

Model No.	Bore Size	Stroke	Rod	Pin to Pin Dimension		Column Load	Estimate Ship Wt.(lbs.)
				Retracted	Extended		
2T2008A	2.0"	8"	1 1/8"	20 1/4"	28 1/4"	FULL PSI	19.1
2T2508A	2.5"	8"	1 1/8"	20 1/4"	28 1/4"	FULL PSI	22.5
2T3008A	3.0"	8"	1 1/4"	20 1/4"	28 1/4"	FULL PSI	26.7
2T3016A	3.0"	16"	1 3/8"	31 1/2"	47 1/2"	FULL PSI	24.5
2T3508A	3.5"	8"	1 1/4"	20 1/4"	28 1/4"	FULL PSI	36.0
2T3516A	3.5"	16"	1 1/2"	31 1/2"	47 1/2"	FULL PSI	46.1
2T4008A	4.0"	8"	1 1/2"	20 1/4"	28 1/2"	FULL PSI	38.0
2T4016A	4.0"	16"	1 3/4"	31 1/2"	47 1/2"	FULL PSI	55.2
2T5008A	5.0"	8"	1 1/2"	22 1/2"	30 1/4"	FULL PSI	48.5
2T5016A	5.0"	16"	2.0"	33 1/2"	49 1/2"	FULL PSI	63.8

ASAE 标准缸 ASAE Standard

2" Bore Size, Non-ASAE Cylinders

Model No.	Stroke	Rod	Pin to Pin Dimension		Column Load (lbs)	Estimate Ship Wt.(lbs.)
			Retracted	Extended		
2T2004	4"	1 1/8"	14 1/4"	18 1/4"	FULL PSI	14.9
2T2006	6"	1 1/8"	16 1/4"	22 1/4"	FULL PSI	16.5
2T2008	8"	1 1/8"	18 1/4"	26 1/4"	FULL PSI	18.1
2T2010	10"	1 1/8"	20 1/4"	30 1/4"	FULL PSI	19.7
2T2012	12"	1 1/8"	22 1/4"	34 1/4"	FULL PSI	21.3
2T2014	14"	1 1/8"	24 1/4"	38 1/4"	FULL PSI	22.9
2T2016	16"	1 1/8"	26 1/4"	42 1/4"	FULL PSI	24.5
2T2018	18"	1 1/8"	28 1/4"	46 1/4"	FULL PSI	26.1
2T2020	20"	1 1/8"	30 1/4"	50 1/4"	FULL PSI	27.7
2T2022	22"	1 1/8"	32 1/4"	54 1/4"	7359	27.7
2T2024	24"	1 1/8"	34 1/4"	58 1/4"	5741	30.9
2T2026	26"	1 1/8"	36 1/4"	62 1/4"	5125	32.5
2T2028	28"	1 1/8"	38 1/4"	66 1/4"	4603	34.1
2T2030	30"	1 1/8"	40 1/4"	70 1/4"	4157	35.7
2T2036	36"	1 1/8"	46 1/4"	82 1/4"	3148	40.5

2 1/2" Bore Size, Non-ASAE Cylinders

Model No.	Stroke	Rod	Pin to Pin Dimension		Column Load ( lbs )	Estimate Ship Wt.(lbs.)
			Retracted	Extended		
2T2504	4"	1 1/8"	14 1/4"	18 1/4"	FULL PSI	17.9
2T2506	6"	1 1/8"	16 1/4"	22 1/4"	FULL PSI	19.8
2T2508	8"	1 1/8"	18 1/4"	26 1/4"	FULL PSI	21.7
2T2510	10"	1 1/8"	20 1/4"	30 1/4"	FULL PSI	23.6
2T2512	12"	1 1/8"	22 1/4"	34 1/4"	FULL PSI	25.5
2T2514	14"	1 1/8"	24 1/4"	38 1/4"	FULL PSI	27.4
2T2516	16"	1 1/8"	26 1/4"	42 1/4"	FULL PSI	29.3
2T2518	18"	1 1/8"	28 1/4"	46 1/4"	FULL PSI	31.2
2T2520	20"	1 1/8"	30 1/4"	50 1/4"	FULL PSI	33.1
2T2522	22"	1 1/8"	32 1/4"	54 1/4"	7194	35.0
2T2524	24"	1 1/8"	34 1/4"	58 1/4"	8750	36.9
2T2526	26"	1 1/8"	36 1/4"	62 1/4"	7811	38.8
2T2528	28"	1 1/4"	38 1/4"	66 1/4"	7015	40.7
2T2530	30"	1 1/4"	40 1/4"	70 1/4"	6335	42.6
2T2536	36"	1 1/4"	46 1/4"	82 1/4"	4798	48.3

3" Bore Size, Non-ASAE Cylinders

Model No.	Stroke	Rod	Pin to Pin Dimension		Column Load ( lbs )	Estimate Ship Wt.(lbs.)
			Retracted	Extended		
2T3004	4"	1 1/4"	14 1/4"	18 1/4"	FULL PSI	21.1
2T3006	6"	1 1/4"	16 1/4"	22 1/4"	FULL PSI	23.3
2T3008	8"	1 1/4"	18 1/4"	26 1/4"	FULL PSI	25.5
2T3010	10"	1 1/4"	20 1/4"	30 1/4"	FULL PSI	27.7
2T3012	12"	1 1/4"	22 1/4"	34 1/4"	FULL PSI	29.9
2T3014	14"	1 1/4"	24 1/4"	38 1/4"	FULL PSI	32.1
2T3016	16"	1 1/4"	26 1/4"	42 1/4"	FULL PSI	34.3
2T3018	18"	1 1/4"	28 1/4"	46 1/4"	12861	36.5
2T3020	20"	1 1/4"	30 1/4"	50 1/4"	11217	38.7
2T3022	22"	1 1/4"	32 1/4"	54 1/4"	9868	40.9
2T3024	24"	1 1/4"	34 1/4"	58 1/4"	18143	43.1
2T3026	26"	1 1/4"	36 1/4"	62 1/4"	16196	45.3
2T3028	28"	1 1/4"	38 1/4"	66 1/4"	14547	47.5
2T3030	30"	1 1/4"	40 1/4"	70 1/4"	13137	49.7
2T3036	36"	1 3/8"	46 1/4"	82 1/4"	9950	56.3
2T3048	48"	1 3/8"	58 1/4"	106 1/4"	6273	69.5

3 1/2" Bore Size, Non-ASAE Cylinders

Model No.	Stroke	Rod	Pin to Pin Dimension		Column Load ( lbs )	Estimate Ship Wt.(lbs.)
			Retracted	Extended		
2T3504	4"	1 1/4"	14 1/4"	18 1/4"	FULL PSI	26.8
2T3506	6"	1 1/4"	16 1/4"	22 1/4"	FULL PSI	29.7
2T3508	8"	1 1/4"	18 1/4"	26 1/4"	FULL PSI	32.6
2T3510	10"	1 1/4"	20 1/4"	30 1/4"	FULL PSI	35.5
2T3512	12"	1 1/4"	22 1/4"	34 1/4"	FULL PSI	38.4
2T3514	14"	1 1/4"	24 1/4"	38 1/4"	FULL PSI	41.3
2T3516	16"	1 1/4"	26 1/4"	42 1/4"	FULL PSI	44.2
2T3518	18"	1 1/4"	28 1/4"	46 1/4"	FULL PSI	47.1
2T3520	20"	1 1/4"	30 1/4"	50 1/4"	FULL PSI	50.0
2T3522	22"	1 1/2"	32 1/4"	54 1/4"	20463	52.9
2T3524	24"	1 1/2"	34 1/4"	58 1/4"	18143	55.8
2T3526	26"	1 1/2"	36 1/4"	62 1/4"	16196	58.7
2T3528	28"	1 1/2"	38 1/4"	66 1/4"	14547	61.6
2T3530	30"	1 1/2"	40 1/4"	70 1/4"	13137	64.5
2T3536	36"	1 1/2"	46 1/4"	82 1/4"	9950	73.2
2T3548	48"	1 1/2"	58 1/4"	106 1/4"	6273	90.6

4" Bore Size, Non-ASAE Cylinders

Model No.	Stroke	Rod	Pin to Pin Dimension		Column Load ( lbs )	Estimate Ship Wt.(lbs.)
			Retracted	Extended		
2T4004	4"	1 1/4"	14 1/4"	18 1/4"	FULL PSI	29.4
2T4006	6"	1 1/4"	16 1/4"	22 1/4"	FULL PSI	33.0
2T4008	8"	1 1/4"	18 1/4"	26 1/4"	FULL PSI	36.6
2T4010	10"	1 1/4"	20 1/4"	30 1/4"	FULL PSI	40.2
2T4012	12"	1 1/4"	22 1/4"	34 1/4"	FULL PSI	43.8
2T4014	14"	1 1/4"	24 1/4"	38 1/4"	FULL PSI	47.4
2T4016	16"	1 1/4"	26 1/4"	42 1/4"	FULL PSI	51.0
2T4018	18"	1 1/2"	28 1/4"	46 1/4"	FULL PSI	54.6
2T4020	20"	1 1/2"	30 1/4"	50 1/4"	FULL PSI	58.2
2T4022	22"	1 1/2"	32 1/4"	54 1/4"	20463	61.8
2T4024	24"	1 1/2"	34 1/4"	58 1/4"	33613	65.4
2T4026	26"	1 1/2"	36 1/4"	62 1/4"	30006	69.0
2T4028	28"	1 1/2"	38 1/4"	66 1/4"	26950	72.6
2T4030	30"	1 3/4"	40 1/4"	70 1/4"	41520	76.2
2T4036	36"	1 3/4"	46 1/4"	82 1/4"	31446	87.0
2T4040	40"	1 3/4"	48 1/4"	86 1/4"	26639	94.2
2T4042	42"	1 3/4"	52 1/4"	94 1/4"	24639	97.8
2T4044	44"	1 3/4"	54 1/4"	98 1/4"	22856	101.4

2T4046	46"	1 3/4"	56 1/4"	102 1/4"	21259	105.0
2T4048	48"	1 3/4"	58 1/4"	106 1/4"	19824	108.6

5" Bore Size, Non-ASAE Cylinders

Model No.	Stroke	Rod	Pin to Pin Dimension		Column Load (lbs)	Estimate Ship Wt.(lbs.)
			Retracted	Extended		
2T5004	4"	1 1/2"	16 1/4"	20 1/4"	FULL PSI	39.1
2T5006	6"	1 1/2"	18 1/4"	24 1/4"	FULL PSI	42.9
2T5008	8"	1 1/2"	20 1/4"	28 1/4"	FULL PSI	46.7
2T5010	10"	1 1/2"	22 1/4"	32 1/4"	FULL PSI	50.5
2T5012	12"	2"	24 1/4"	36 1/4"	FULL PSI	54.3
2T5014	14"	2"	26 1/4"	40 1/4"	FULL PSI	58.1
2T5016	16"	2"	28 1/4"	44 1/4"	FULL PSI	61.9
2T5018	18"	2"	30 1/4"	48 1/4"	FULL PSI	65.7
2T5020	20"	2"	32 1/4"	52 1/4"	FULL PSI	69.5
2T5024	24"	2"	36 1/4"	60 1/4"	57342	77.1
2T5030	30"	2"	42 1/4"	72 1/4"	41520	88.5
2T5036	36"	2"	48 1/4"	84 1/4"	31446	99.9